

# The Five-Tube Coin Changer

*~Simple Operation & Easy Maintenance~*

## CCM5G Series 5-Tube Coin Changer EXCLUSIVE FEATURES



### ■ Five Tubes:

More change capacity eliminates possibility of change starvation. Sell more products and eliminate costly service calls. Swing open rear tube makes for easy collection and replenishment of change.

### ■ Front Tube Cassette:

Self recognition by coin changer means no programming needed by service technician, thus no possibility of errors being made in programming.

Just exchange the cassette tube depending on vend price and you are ready to go!

### ■ No Tools Required to Disassemble

90% of coin changer requires no tools to disassemble, resulting in easy maintenance even in a field location.

### ■ Payout System:

Payout three coins simultaneously which increases throughput in high volume locations and reduces motor wear.

### ■ Smart Payout:

Makes sure coin was paid out and if not, will try to pay that coin out one more time, resulting in less service calls.

### ■ Anti-Salting Systems:

Our uniquely designed diversion channel will protect your changer and vendor from salt water damage and vandalism.

### ■ Memory Back-Up:

The coin changer will retain its memory in case of a power failure.

### ■ Swing Open Payout Base:

No tools needed to remove payout base for cleaning or to remove foreign material.

### ■ Last Coin Payout:

No dead inventory.



### Need more change?

#### Satellite Tube

Ready to connect Satellite Tube with an existing CCM5G 5 tube coin changer.

No additional software or hardware change required.

# CCM5G Series Coin Changer



## Specifications

Interface	Multi-Drop-Bus (M.D.B.)
Operating Voltage	+34VDC
Power Consumption	Standby 0.10A
Operating State	Motor Operation 0.66A Peak Max. 5sec. 0.92A
Operating Temperature Range	5°F(-15°C)to140°F(+60°C)
Insulation Resistance	20 M Ohm or more
Weight	4.2 Lbs. (1.9 Kg.)
Dimensions	HxWxD:14.83"x5.43"x3.23" (376mmx137mmx82mm)
Number of Motors	1 Motor-15VDC
Number of Solenoids	5 for Coin Selection-15VDC
Coin Acceptance	US: 5¢, 10¢, 25¢, \$1 CAN: 5¢, 10¢, 25¢, \$1, \$2 Switch Selectable for US only, Canadian only, or both
Cassette Tube	US-1 Cassette: 1N,1D,3Q US-2 Cassette: 2N,2D,1Q US-4 Cassette: 1N,1D,2Q,1\$ US-5 Cassette: 2N,3D

**CONLUX**  
NIPPON CONLUX CO.,LTD.